

# MetroCount<sup>®</sup> Product Brochure

## RELIABLE TRAFFIC MONITORING

Automatic Traffic Counters/Classifiers. Data Analysis Software.



# Automatic Traffic Counters/Classifiers



## RoadPod® VT

Portable traffic counter with two rubber tubes for short-term road traffic surveys.

---



## RoadPod® VT4

Portable traffic counter with four rubber tubes, enabling comprehensive data collection from highways and other multi-lane carriageways.

---



## RoadPod® PhaseT

This counter is attached to traffic lights or rail crossings, using rubber tubes and an optical fibre connection to gather traffic data in relation to signal phases.

---



## RoadPod® VP

Permanent vehicle counter with piezoelectric sensors. Ideal for major roads with heavy flows to provide continuous, lane by lane, seasonal data.

---



## RoadPod® VL

Permanent vehicle counter using inductive loops for recording class, speed and volume data (model VL5810) or just traffic volumes (model VL5805).

---



## RoadPod® VM

The RoadPod® VM patented magnetometers are small, unobtrusive and off-grid vehicle counters that provide real-time data on traffic movements.

---



## RidePod® BT

Portable bike counter with rubber tubes for short-term bicycle & e-scooter surveys.

---



## RidePod® BP

Permanent counter gathering data on bikes, e-scooters & pedestrians with embedded piezoelectric sensors.

# REVOLUTIONISING TRAFFIC SURVEY MANAGEMENT AND DATA ANALYTICS



ATLYST<sup>®</sup> by MetroCount<sup>®</sup>

# TRAFFIC ANALYTICS

## INDIVIDUAL VEHICLE DATA

ATLYST uses the familiar and trusted MTE algorithms to generate statistics using each vehicle.

## INTERACTIVE MAP VIEW

ATLYST uses editable colour schemes and three data layers (Volume, Speed and Class) to quickly and clearly display network-wide traffic behaviour, track changes and identify unusual patterns.

## AUTOMATED REPORT CREATION


Get access to a detailed view of each survey site with one click, including the 85th percentile speed, ADT, peak hours, virtual days, etc. Apply filters to quickly reach specific information.

## SMART MULTI-SITE COMPARISON

Store and access traffic data at the same location to quickly see changes over years. Select neighbouring locations for multi-site comparison.

## VARIOUS DATA FORMATS

ATLYST securely archives your raw data files and exports statistics in PDF, CSV and XLSX formats.



# DATA & SURVEY MANAGEMENT

## AUTOMATED DATA VALIDATION

Drag and drop your files into ATLYST to start an automated data quality control process. You will be notified if any anomalies are found.

## SMART SITE EDITING

ATLYST uses built-in tools to enable easy changes to site details or merging of multiple datasets at neighbouring locations into the same site.

## CONSISTENT SURVEYS

Easily create and send MTE Site Lists to your field team and contractors, ensuring replicated surveys use the same site details. Save time and keep your data organised.

## SECURE DATAFILE ARCHIVE

Build your archive of raw data files in the Cloud for quick access and download from any computer, at any time, while retaining full data ownership.

## QUICK GIS PLATFORM EXPORTS

Bulk export your data into CSV files for easy transfer to other GIS and Asset Management applications.

### Edit Site

Name

Cycle 51471

Description


South Beach Cycle Path

Asset Management Id

51471

☐ Continuous Data

☒ Pedestrian Included



CANCEL RESET SAVE



# Remote Data Services



Opting for Remote Data Services allows your sites to be remotely managed by experienced MetroCount traffic data analysts. Retain full ownership of your data but say goodbye to manually checking sensors and downloading, quality checking and analysing data. We'll do it all for you through a secure sever and send you alerts, raw data or cutomised reports as you choose.

If you prefer to remotely manage your sites yourself, the Remote Access Link allows sensors checks and data download from your desk.



# RoadPod® VT

## Portable vehicle counter & classifier

VOLUME | SPEED | AXLE-BASED CLASSIFICATION | HEADWAY & TRAFFIC GAP | DIRECTION



The RoadPod® VT system is used in over 120 countries. Renowned for recording up to 4 million vehicle axles with greater than 99% accuracy, it is the best solution for short-term traffic monitoring on the market.

Economical, easy to install & replace, two pneumatic tubes record traffic under a broad range of conditions.

**Sensors:** Two pneumatic tubes

**Memory:** Flash, up to 2 million vehicles

**Battery life:** Up to 4 years

**Enclosure:** Stainless steel road case

**Remote Access Link:** Optional



# RoadPod® VT4

## Portable 4-tube counter & classifier

VOLUME | SPEED | AXLE-BASED CLASSIFICATION | HEADWAY & TRAFFIC GAP | DIRECTION



The RoadPod® VT4 is the solution for collecting comprehensive and accurate data from multi-lane roads, often used for monitoring highways.

With four tubes, one counter collects two datasets from two lanes, regardless of traffic direction. A combination of VT4s can simultaneously monitor up to eight traffic lanes in all weather and lighting conditions.

**Sensors:** Four pneumatic tubes

**Memory:** Flash, up to 4 million axles

**Battery life:** Up to 2 years

**Enclosure:** Stainless steel road case

**Remote Access Link:** Optional





# RoadPod® PhaseT Vehicle behaviour at traffic signals

VOLUME | SPEED | AXLE-BASED CLASSIFICATION | HEADWAY & GAP | LIGHT VIOLATIONS

The RoadPod® PhaseT simultaneously collects traffic data (via tubes) and signal timings (via fibre optic cable) to paint a clear picture of road activity at traffic signals and rail crossings.

The PhaseT is often used to assess reaction times during the warning (amber) phase, to identify potential infringements, or to evaluate the effectiveness of signals. Data collected will highlight safety risks of red and orange light violations and speeding.

**Sensors:** Two pneumatic tubes and one optical fibre

**Memory:** Flash, up to 4 million axles

**Battery life:** Up to 2 years

**Remote Access Link:** Optional



# RoadPod® VP

## Permanent piezoelectric counter

VOLUME | SPEED | AXLE-BASED CLASSIFICATION | HEADWAY & TRAFFIC GAP | DIRECTION



The RoadPod® VP offers the highest level of accuracy and detail for a permanent monitoring solution. Designed for multi-lane data collection, the system uses two low profile piezoelectric strips embedded in the pavement.

The RoadPod VP is ideal for identifying seasonal trends, traffic changes over time, and determining adjustment factors for short-term traffic surveys.

**Sensors:** Two piezoelectric strips

**Memory:** Flash, up to 4 million axles

**Enclosure:** Stainless steel cabinet with solar panel

**Remote Access Module:** Optional



# RoadPod® VL

## Permanent inductive loop counter

VOLUME | SPEED | LENGTH-BASED CLASSIFICATION | HEADWAY & TRAFFIC GAP | DIRECTION

The RoadPod® VL series uses loop sensors to detect vehicles entering and leaving an inductive field. This system can be economically retrofitted to existing sensors.

The VL5810 model provides vehicle volume, class, speed, direction and other traffic-related data.

The VL5805 model is ideal when volume data is sufficient.

**Sensors:** Two or four inductive loops

**Memory:** Up to 500,000 classified vehicles

**Enclosure:** Stainless steel cabinet with solar panel

**Remote Access Module:** Optional



# RoadPod® VM

## Magnetometer counter

VOLUME | SPEED | LENGTH-BASED CLASSIFICATION | HEADWAY & TRAFFIC GAP | DIRECTION

RoadPod® VMs work in an array to accurately count vehicles, monitor speeds and classify vehicle type based on the length of each passing vehicle. Gap and headway information is also available and all data is precisely time-stamped.

The RoadPod® VM was designed to be the simplest and fastest traffic sensor to install on sealed roads.

**Sensors:** Three or four magnetometers

**Memory:** Up to 500,000 classified vehicles

**Remote Access Module:** Required

**ATLYST:** Required





VOLUME | SPEED | CLASS | HEADWAY & TRAFFIC GAP | TRUE DIRECTION | BICYCLE CLUSTERS

The RidePod® BT is optimised for detecting bicycle and e-scooter axles with thin-walled pneumatic tubes for increased sensitivity.

In the MTE software included, every axle hit is used to accurately identify individual bicycles in clusters and distinguish bikes and e-scooters from all other traffic. This results in accurate volume, speed and true direction statistics.

**Sensors:** Two thin-walled pneumatic tubes

**Memory:** Flash, up to two million bicycles

**Remote access:** Optional



# RidePod® BP

## Bicycle, scooter & pedestrian counter

VOLUME | SPEED | HEADWAY & GAP | TRUE DIRECTION | BIKE CLUSTERS | PEDESTRIAN VOLUMES



The RidePod® BP is the device of choice for sustainable transport planning. Using two sensitive piezoelectric strips, this system is not affected by weather, light or temperature, ensuring accurate, continuous data gathering.

The sensors simultaneously detect and time-stamp each bicycle or scooter axle hit, accurately classifying even when in clusters. Pedestrian volumes are reliably recorded with analysis occurring afterwards in the MTE software.

**Sensors:** Two piezoelectric strips

**Memory:** Flash, up to 1 million bikes and e-scooters

**Enclosure:** Stainless steel cabinet with solar panel

**Remote data services:** Optional





MTE® is recognised as the most advanced traffic analysis software on the market. It securely processes time-stamped data post-collection, allowing for extreme accuracy and flexibility when creating reports.

The software prevents dataset tampering, runs detailed quality checks and offers hundreds of filtering options.

## Reporting

- Multi-lane, multi-dataset analysis.
- Detailed data quality checking.
- 30+ built-in global classification schemes.
- Template reports including ADT, vehicle class breakdown, 85th percentile speed, hourly vehicle volumes, peak hour analysis and more.
- Export to Excel, GIS systems and Google Earth.

## Hardware management

- Dynamic prediction of battery life.
- Easy counter set up at the roadside.
- Survey setup and mapping features.
- Remote sensor diagnostics and data download.
- Touch-screen support.

## Individual Vehicle Report Example

Date	Time	Speed	Wheebase	Headway	Gap	Axles	Groups	RHO	Vehicle Class	
YYYY-MM-DD	hh:mm:ss	Km/h	M	M	M	No.	No.	%	Visual	Representation
2018-05-20	13:16:01	84.44	13.88	28.6	28.5	6	3	1.00	ART6	o oo ooo
2018-05-20	13:16:03	78.95	2.67	1.9	1.3	2	2	1.00		SV o o
2018-05-20	13:16:05	80.51	2.52	2.3	2.2	2	2	1.00		SV o o
2018-05-20	13:16:35	71.94	19.79	19.9	19.8	6	5	1.00	ART6	o o oo o o



[info@metrocount.com](mailto:info@metrocount.com)

Australia & Oceania: +61 8 9430 6164

UK & Africa: +44 20 8782 8999

Americas: +1 301 497 6101

Europe: +31 10 268 01 84