

Award winning and critically acclaimed product!



The world's first in-tundish Audible, Visual, Water Detection and Temperature **Sensing Alarm** for PRV discharge and water tank overflows

If alarm sounds contact your

professional installer/engineer

MUTE: Hold 2-3 seconds RESET: 1st Mute & release

2nd Hold 8 seconds

WORLD'S FIRST

Key features:

- Audible (72dBA) and visual alarm unit for relief valve discharges or water tank overflow
- Operational features: Set-up check/Unit on, Alarm stage warning, Battery condition, Auto low power alert
- Auto-mute/Auto-reset with manual override
- Senses water and temperature in four stages to aid fault diagnosis (see over)
- Helps save water and energy
- · Complies with G3 Regulations to aid visually and mobility impaired
- Simple clip-on design and fitted within seconds on any hotun tundish
- Battery operated (2032 coin cell, supplied with unit.) Requires no specialist electrical knowledge to fit

Patented • Pioneering • Products

www.hotun.co.uk

No other dry-trap tundish on the market has this vital-for-diagnosis unique benefit.

> Water sits on the top of the valve, forming a small, easily seen, visible puddle even after the PRV has stopped dripping, without having to remove the tundish from the pipeline!

hotun detect gives the user four different alerts depending on the temperature of the water as follows:

	Temp	Audible	Visual Description	Visual Representation	Repeat (seconds)
Normal Operation	N/A	None	1 x Green flash	•	8
Stage 1 Warning	Up to 20°C	1 beep	1 x Red flash	•	20
Stage 2 Warning	21 - 60°C	2 beeps	2 x Red flash	••	20
Stage 3 Warning	61 – 85°C	3 beeps	3 x Red flash	•••	20
Stage 4 Warning	>85°C	2 long beeps	2 x long Red flashes	••	20
Low Battery Warning	N/A	1 beep	Rapid Red/Green alternating	•	30
Mute	N/A	None	1 x Red flash	•	20

