

# NAVIGATOR<sup>®</sup>

LEADING THE WAY

## DUAL SLEEVE LEVER BALL VALVES



## INTRODUCING DUAL SLEEVE LEVER BALL VALVES FROM NAVIGATOR<sup>®</sup>

**The Navigator range of Dual Sleeve Lever Ball Valves means an end to stocking two types for hot or cold. Each valve is supplied with our unique (patent pending) blue and red sleeves. The installer simply chooses which sleeve to use, and it clips securely onto the handle – no tools required!**

Our standard ball valves have compression fitting ends and include olives. All our lever ball valves are WRAS approved for use with potable water.

The new MB Pressfit valves are full bore and are compatible with all M type press fittings. Also with full WRAS approval, these too have the dual sleeves and complement our range of MB press fittings perfectly.

### FULL BORE DUAL LEVER BALL VALVE



### LIGHT PATTERN DUAL LEVER BALL VALVE



### PRESSFIT DUAL LEVER BALL VALVE



## FULL BORE DUAL LEVER BALL VALVES

| Code      | Size | Lever Length | Body Length | H    | Kgs   |
|-----------|------|--------------|-------------|------|-------|
| BFLBVD-15 | 15mm | 106.5        | 72          | 50.5 | 0.240 |
| BFLBVD-22 | 22mm | 106.5        | 79          | 54.9 | 0.328 |
| BFLBVD-28 | 28mm | 115          | 87.7        | 57.3 | 0.509 |



15MM - BFLBVD-15



22MM - BFLBVD-22



28MM - BFLBVD-28

### Full Bore Technical Data

|                          |              |
|--------------------------|--------------|
| Field of Application     | Water        |
| Max. Working Pressure    | 10 Bar       |
| Max. Working Temperature | 0°C to +70°C |
| Specification            | BS 6675      |

WRAS  
Approved



## LIGHT PATTERN DUAL LEVER BALL VALVES

| Code        | Size | Lever Length | Body Length | H    | Kgs   |
|-------------|------|--------------|-------------|------|-------|
| BFLBVDLP-15 | 15mm | 86           | 64.2        | 41.7 | 0.200 |
| BFLBVDLP-22 | 22mm | 86           | 70          | 42.5 | 0.260 |
| BFLBVDLP-28 | 28mm | 103          | 70          | 54.7 | 0.449 |



15MM - BFLBVDLP-15



22MM - BFLBVDLP-22



28MM - BFLBVDLP-28

### Light Pattern Technical Data

|                          |              |
|--------------------------|--------------|
| Field of Application     | Water        |
| Max. Working Pressure    | 10 Bar       |
| Max. Working Temperature | 0°C to +70°C |

WRAS  
Approved



## PRESSFIT WATER DUAL LEVER BALL VALVES

| Code       | Size | Length (mm) | Width (mm) | Height (mm) | Weight (g) |
|------------|------|-------------|------------|-------------|------------|
| PFWLBVD-15 | 15mm | 134         | 30.5       | 58.6        | 204        |
| PFWLBVD-22 | 22mm | 152         | 38.5       | 72.1        | 327        |
| PFWLBVD-28 | 28mm | 158         | 47         | 83.5        | 499        |



15MM - PFWLBVD-15



22MM - PFWLBVD-22



28MM - PFWLBVD-28

### Full Bore Technical Data

|                          |              |
|--------------------------|--------------|
| Field of Application     | Water        |
| Max. Working Pressure    | 10 Bar       |
| Max. Working Temperature | 0°C to +70°C |
| Specification            | BS 6675      |

WRAS  
Approved

